



## REQUEST FOR QUOTATION

Date: October 06, 2022 RFQ No.: 2022-288

| Address:  |     |
|---|-----|
| Business Permit No.:  |     |
| Please quote your best offer for the item/s described below, subject to the Terms and Conditions provided at the dorsal portion of this request for quotation. Submit your quotation duly signed by you or your duly authorized representative not later than | RAY |

RAV R. ELEVAZO, CESE, MNSA Chairman, Bids & Awards Committee

After having carefully read and accepted the Terms and Conditions, I/we submit our quotation/s for ie item/s as follows:

|  |  |           |     |                          |             | OFFER |    |  |
|--|--|-----------|-----|--------------------------|-------------|-------|----|--|
| ITEM DESCRIPTION   | ITEM DESCRIPTION  Quantity (QTY)  Approved Budget for the Contract |           | 1   | Compliance<br>Specificat | REMARKS     |       |    |  |
| JRPOSE: FOR THE OFFICIAL USE OF LEGAL AFFAIRS SERVICES   |  | 91,800.00 | QTY |                          | Total Price | Yes   | No |  |
|  |  |           |     |                          |             |       |    |  |
| OM HDMI 4K Ultra HD High Speed Cable   | 3 pcs  | 1         |     | 1 1                      |             |       |    |  |
| ompatible Devices  |  | 1         |     |                          |             |       |    |  |
| ple, Microsoft, Acer, Sony Samsung et.   |  | 1         |     | 1                        |             |       |    |  |
| gher video resolutions support a range of high resolutions and faster refresh  |  |           |     |                          |             |       |    |  |
| tes including 8K60Hz and 4K120Hz for immersive viewing and smooth fast-  |  | 1         |     |                          |             |       |    |  |
|  |  | 1         |     |                          |             |       |    |  |
| ion detail. Resolutions up to 10K are also supported for commercial AV, and  |  | 1         |     |                          |             |       |    |  |
| Justrial and specialty usages.   |  | 1         |     |                          |             |       |    |  |
| mamic HDK support ensures every moment of a video is displayed at its ideal  |  | i i       |     | 1                        |             | 1     | 1  |  |
| lues for depth, detail, brightness, contrast and wider color gamuts—on a scene   |  |           |     |                          |             |       |    |  |
| scene or even a frame-by-frame basis.  |  |           |     |                          |             |       |    |  |
| ortable Speaker  | 1 no   |           |     |                          |             |       |    |  |
| aximum music playing time (nrs) 18   | 1 pc   | 1         |     |                          |             |       |    |  |
| tput power (W) 240   |  | 1         |     |                          |             |       |    |  |
| dio Specifications   |  | 1         |     |                          |             |       |    |  |
| mamic frequency response range (Hz) 45 Hz - 20 KHz (-6 dB)   |  | 1         |     |                          |             | 1     |    |  |
| mensions   |  |           |     |                          |             |       |    |  |
| mensions (cm) 68.8 x 32.6 x 36.8   |  | 1         |     | 1                        |             | 4     | 1  |  |
| mensions (in) 27 x 12.8 x 14.5   |  |           |     |                          |             |       |    |  |
| eight (kgs) 17.42  |  | 1         |     |                          |             | [     |    |  |
| eight (ibs) 38.4   |  | 1         |     |                          |             |       |    |  |
| entrol and Connection Specifications   |  | 1         |     | 1                        |             |       |    |  |
| petooth profiles A2DP 1.3, AVRCP 1.6   |  |           |     |                          |             |       |    |  |
| uetooth frequency 2.4 – 2.48GHz  |  |           |     | 1                        |             |       |    |  |
| uetooth transmitted modulation GFSK, π/4 DQPSK, 8DPSK  |  | 1         |     |                          |             |       |    |  |
| uetooth transmitter power 15dBm (EIRP)   |  | 1         |     |                          |             |       |    |  |
| to the state of th |  | 1         |     |                          |             |       |    |  |
| uetooth version 5.1  |  | l i       |     | i i                      |             | 1     | 1  |  |
| ittery   |  | 1         |     | 1                        |             |       |    |  |
| narging time (hrs) 3.5   |  | 1         |     |                          |             | 1     |    |  |
| atures   |  | 1         |     |                          |             |       |    |  |
| 5 mm audio cable Input   |  | 1         |     |                          |             |       |    |  |
| uetooth  |  | 1         |     |                          |             | 1     |    |  |
| arging cable   |  |           |     | 1                        |             |       |    |  |
| raoke function   |  |           |     |                          |             |       |    |  |
| thtshow  |  |           |     |                          |             |       |    |  |
| lashproof  |  | į į       |     |                          |             | 1 .   | Į  |  |
| ireless  |  |           | 9   |                          |             | 1     |    |  |
| chargable battery  |  | 1         | 1   | 1                        |             | 1     |    |  |
| ue Wireless  |  |           |     |                          |             |       |    |  |
|  |  |           |     |                          |             | 1     |    |  |
| deo Mixer Switcher   | 1 pc   |           |     |                          |             | 1     |    |  |
| th 4 CH HDMI inputs and 1 HDMI output, all of them support 1080p. For live   |  |           |     | 1                        |             |       | -  |  |
| eaming, there is a USB3.0 interface . Plus, the LAN port for controlling and   |  |           |     |                          |             | 1     |    |  |
| grading; for audio, it has 2 interfaces, one for input, and the other one for  |  |           |     |                          |             |       |    |  |
| tput.  |  | 1         |     |                          |             | į .   | j  |  |
| s able stream any one from the 4 HDMI inputs to any live broadcasting  |  |           |     |                          |             |       | 1  |  |
| tform via third party live streaming software such as OBS . Simply connect the   |  |           |     |                          |             |       | 1  |  |
| elworld Livepro L1 and you can switch live between 4 high quality video  |  |           |     |                          |             |       |    |  |
| nera inputs for dramatically better quality images.  |  |           |     |                          |             |       |    |  |
| The Later Co. T. C. Company (America) as well as the modern than the Co. C.  |  |           |     |                          |             |       |    |  |
| nnidirectional Microphone  | 1 pc   |           |     |                          |             | 1     | 1  |  |
| npatible with Windows and Mac Computers  |  |           |     |                          |             |       |    |  |
| le-capsule design  |  |           |     |                          |             |       |    |  |
| reo, cardioid, omnidirectional, and bi-directional polar patterns  |  | 1         |     | 1                        |             | 1     |    |  |
| Bit/48 kHz Resolution  |  | 1         |     | 1                        |             | 1     | 1  |  |
| ting function  |  |           |     |                          |             |       | 1  |  |
| " Headphone Monitoring Jack  |  |           |     |                          |             | 1 1   | 1  |  |
| rency-Free Monitoring  |  |           |     | 1                        |             |       |    |  |
| sktop Stand  |  |           |     |                          |             | 1     |    |  |
|  |  |           |     |                          |             |       |    |  |
| rable all metal construction   |  |           |     |                          |             |       |    |  |

| 1  | 1     | 1 | I        | l  | 1 | l                           | ľ   | l |
|--|-------|---|----------|----|---|-----------------------------|-----|---|
| Fluid head Tripod  | 2 pcs |   |          |    |   | i                           |     |   |
| Carnera Plate  | •     |   |          |    |   | ŀ                           |     |   |
| - Camera Plate Features: Skiding Balance Plate,  |       | ļ |          |    | İ |                             |     | i |
| Quick Release  |       | 1 | ļ        | }  | 1 |                             |     | į |
| - Camera Plate Type: Sideload Plate  |       | 1 | ľ        | ļ  |   | ŀ                           |     |   |
| - Camera Mounting Screw : 1 x 1/4"-20 Male with  |       | 1 | ļ.       | Į. |   |                             |     | ŀ |
| Locating Pin   | J     | j | ]        | ]  |   |                             |     | : |
| - 1 x 3/8"-16 Male with Locating Pln   |       |   | Ì        | Ì  | Ì | į                           | ĺ   | j |
| - Safety Lock: Yeş   |       |   | ŀ        |    |   | ļ                           |     | ŀ |
| - Plate Dimensions: 5.71 x 1.97" / 145 x 50 mm   |       |   |          |    |   |                             |     |   |
| Head   |       |   |          |    |   |                             |     |   |
| - Base Mount: 75 mm Haif Ball  | 1     |   | 1        |    |   |                             | 1   |   |
| - Pan Handle Fittings: 2 x Rosette   |       | ŀ |          |    |   |                             |     |   |
| - Bubble Level: 1  |       |   |          |    |   |                             |     |   |
| - Base Diameter: 2.95" / 75 mm   |       |   | ł        |    |   |                             |     |   |
| - Pan &amo: Tilt   | ļ     | ļ | !        |    | ļ |                             | J   |   |
| - Drag Type: Fluid   |       |   |          | 1  |   | ĺ                           | l   |   |
| - Vertical Tilt: +90° to -70°  |       |   | 1        | 1  | ł |                             | į   |   |
| - Panning Range: 360*  |       |   | l        |    |   |                             |     |   |
| - Independent Pan Lock: Yes  |       | + | ŀ        | l  | 1 |                             |     | • |
| - Independent Tilt Lock: Yes   | ŀ     |   | ř        |    |   |                             |     |   |
| Legs   |       |   |          |    | 1 |                             |     |   |
| - Leg Lock Type: Flip Lock   |       |   |          | ŀ  |   |                             |     |   |
| - Leg Positions: 3 Positions   |       | ; | ŀ        |    |   |                             |     |   |
| - independent Leg Spread: No   |       | j | ļ        |    |   |                             |     |   |
| - Leg Sections: 3  | 1     |   | <u> </u> | }  | { |                             |     |   |
| - Leg Diameter: 0.87" / 22 mm (Maximum)  |       |   | ŀ        |    |   |                             |     |   |
| - 0.55" / 14 mm (MInimum)  |       |   |          |    |   |                             |     |   |
| - Feet Features: Rubber, Retractable, Spiked   |       |   |          |    |   |                             |     |   |
| - Spreader: Mid-Level (Included)   |       |   |          |    |   |                             |     |   |
| General  |       |   |          |    |   |                             |     |   |
| - Load Capacity: 17.6 lb / 7.98 kg   |       |   |          |    |   |                             |     |   |
| - Maximum Working Height: 60.2; / 153 cm   |       |   |          |    |   |                             |     |   |
| - Minimum Working Height: 30.31 / 77 cm  | i     |   |          |    |   |                             |     |   |
| - Closed Length: 28.3 / 72 cm  | 1     | } |          | 1  | } |                             | ,   |   |
| - Materials: Aluminum  |       |   |          | 1  |   |                             |     |   |
| - Weight: 8.82 lb / 4 kg   | ļ     |   |          | i  | 1 |                             |     |   |
| - Packaging Info   |       |   |          |    | i |                             |     |   |
| - Package Weight: 12.485 lb  |       |   |          | !  |   |                             |     |   |
| - Box Dimensions (LxWxH): 34.1 x 7.6 x 7.4   | i i   |   |          |    | 1 |                             |     |   |
|  |       |   |          |    |   |                             |     |   |
|  |       |   |          |    |   |                             |     |   |
| ***Nothing Fallows***  | J     | 1 |          |    | 1 |                             |     |   |
| Payment Terms: 30 Days After Complete Delivery   | Ì     | j |          |    | Ì | i                           | i ' | į |
| Delivery Period: 30 days   |       |   |          |    |   |                             |     |   |
| Note: •Quoted price/s must be VAT inclusive.   |       | 1 |          |    |   |                             | l., |   |
| Supplier must have a Land Bank of the Phil. Account.   |       |   |          |    |   |                             |     |   |
| Supplier must submit a sealed quotation.   |       |   |          |    |   |                             |     |   |
| <ul> <li>Sealed quotation must be submitted together with the following company Profile, DTI/SEC Registration, Business/Mayor's</li> </ul> |       |   |          |    |   | Signature over Printed Name |     |   |

and PhilGEPS Certificate of Membership

| <br>Canvasser | <br> |
|---------------|------|

| Contact Numbers (Landline and/or |  |
|----------------------------------|--|
| Celiphone Nos.)/E-mail address   |  |

## TERMS AND CONDITIONS

- 1. Bidders shall provide correct and accurate information required in this form.
- Price quotations/s must be valid for a period of Thirty (30) calendar days from the date of submission.
   Price quotations, to be denominated in Philippine peso shall include all taxes.
- 4. Quotations exceeding the Approved Budget for the Contract shall be rejected.
- 5 Award of contract shall be made to the lowest quotation (for goods and infrastructure) or, the highest rated offer (for consulting services) which complies with the minimum technical specifications and other terms and conditions stated herein.
- 6. Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by you or any of your duty authorized representative/s.
- 7. The items shall be delivered within \_\_\_\_\_\_ working days from receipt of Purchase/Job Order.
  8. The CDA-CO shall have the right to inspect and/or to test the goods
- 9. Submit your sealed quotation by mail or through your messenger addressed to the Cooperative Development Authority, 827 Aurora Bivd., Brgy. Immaculate Concepcion, Quezon City.
- 10. The Cooperative Development Authority reserves the right to accept or reject any or all quotations, waive any informality or technically therein and award to any firm whose proposal is deemed most advantageous to the government.